

NAME

CURLINFO_HTTP_VERSION – HTTP version used in the transfer

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_getinfo(CURL *handle, CURLINFO_HTTP_VERSION, long *p);
```

DESCRIPTION

Pass a pointer to a long to receive the version used in the last http transfer done using this handle. The returned value is `CURL_HTTP_VERSION_1_0`, `CURL_HTTP_VERSION_1_1`, `CURL_HTTP_VERSION_2_0`, `CURL_HTTP_VERSION_3` or 0 if the version cannot be determined.

PROTOCOLS

This functionality affects http only

EXAMPLE

```
int main(void)
{
    CURL *curl = curl_easy_init();
    if(curl) {
        CURLcode result;
        curl_easy_setopt(curl, CURLOPT_URL, "https://example.com");
        result = curl_easy_perform(curl);
        if(result == CURLE_OK) {
            long http_version;
            curl_easy_getinfo(curl, CURLINFO_HTTP_VERSION, &http_version);
        }
        curl_easy_cleanup(curl);
    }
}
```

AVAILABILITY

Added in curl 7.50.0

RETURN VALUE

curl_easy_getinfo(3) returns a CURLcode indicating success or error.

CURLE_OK (0) means everything was OK, non-zero means an error occurred, see *libcurl-errors(3)*.

SEE ALSO

CURLINFO_RESPONSE_CODE(3), **curl_easy_getinfo(3)**, **curl_easy_setopt(3)**