

NAME

CURLINFO_RTSP_CSEQ_RECV – last received RTSP CSeq

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_getinfo(CURL *handle, CURLINFO_RTSP_CSEQ_RECV, long *cseq);
```

DESCRIPTION

Pass a pointer to a long to receive the most recently received CSeq from the server. If your application encounters a *CURLE_RTSP_CSEQ_ERROR* then you may wish to troubleshoot and/or fix the CSeq mismatch by peeking at this value.

PROTOCOLS

This functionality affects rtsp only

EXAMPLE

```
int main(void)
{
    CURL *curl = curl_easy_init();
    if(curl) {
        CURLcode result;
        curl_easy_setopt(curl, CURLOPT_URL, "rtsp://rtsp.example.com");
        result = curl_easy_perform(curl);
        if(result == CURLE_OK) {
            long cseq;
            curl_easy_getinfo(curl, CURLINFO_RTSP_CSEQ_RECV, &cseq);
        }
        curl_easy_cleanup(curl);
    }
}
```

AVAILABILITY

Added in curl 7.20.0

RETURN VALUE

curl_easy_getinfo(3) returns a CURLcode indicating success or error.

CURLE_OK (0) means everything was OK, non-zero means an error occurred, see *libcurl-errors(3)*.

SEE ALSO

CURLINFO_RTSP_SERVER_CSEQ(3), *curl_easy_getinfo(3)*, *curl_easy_setopt(3)*