

NAME

CURLINFO_TOTAL_TIME – total time of previous transfer

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_getinfo(CURL *handle, CURLINFO_TOTAL_TIME, double *timep);
```

DESCRIPTION

Pass a pointer to a double to receive the total time in seconds for the previous transfer, including name resolving, TCP connect etc. The double represents the time in seconds, including fractions.

When a redirect is followed, the time from each request is added together.

See also the TIMES overview in the *curl_easy_getinfo(3)* man page.

PROTOCOLS

This functionality affects all supported protocols

EXAMPLE

```
int main(void)
{
    CURL *curl = curl_easy_init();
    if(curl) {
        CURLcode result;
        double total;
        curl_easy_setopt(curl, CURLOPT_URL, "https://example.com/");
        result = curl_easy_perform(curl);
        if(result == CURLE_OK) {
            result = curl_easy_getinfo(curl, CURLINFO_TOTAL_TIME, &total);
            if(result == CURLE_OK) {
                printf("Time: %.1f", total);
            }
        }
        /* always cleanup */
        curl_easy_cleanup(curl);
    }
}
```

AVAILABILITY

Added in curl 7.4.1

RETURN VALUE

curl_easy_getinfo(3) returns a CURLcode indicating success or error.

CURLE_OK (0) means everything was OK, non-zero means an error occurred, see *libcurl-errors(3)*.

SEE ALSO

CURLINFO_TOTAL_TIME_T(3), **CURLOPT_TIMEOUT(3)**, **curl_easy_getinfo(3)**, **curl_easy_setopt(3)**