

NAME

CURLINFO_XFERS_CURRENT – Number of easy handles currently added

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLMcode curl_multi_get_offt(CURLM *handle, CURLINFO_XFERS_CURRENT,  
                             curl_off_t *pvalue);
```

DESCRIPTION

Returns the number of easy handles currently added to the multi handle. This does not include already removed handles. It does include internal handles that get added for tasks (like resolving via DoH, for example).

For the total number of easy handles ever added to the multi, see *CURLINFO_XFERS_ADDED(3)*.

DEFAULT

n/a

PROTOCOLS

This functionality affects all supported protocols

EXAMPLE

```
int main(void)  
{  
    CURLM *m = curl_multi_init();  
    curl_off_t value;  
  
    curl_multi_get_offt(m, CURLINFO_XFERS_CURRENT, &value);  
}
```

AVAILABILITY

Added in curl 8.16.0

RETURN VALUE

curl_multi_get_offt(3) returns a CURLMcode indicating success or error.

CURLM_OK (0) means everything was OK, non-zero means an error occurred, see *libcurl-errors(3)*.

SEE ALSO

CURLINFO_XFERS_PENDING(3), *CURLINFO_XFERS_RUNNING(3)*