

NAME

CURLMOPT_PIPELINING_SITE_BL – pipelining host block list

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLMcode curl_multi_setopt(CURLM *handle, CURLMOPT_PIPELINING_SITE_BL,
                             char **hosts);
```

DESCRIPTION

No function since pipelining was removed in 7.62.0.

Pass a **hosts** array of char *, ending with a NULL entry. This is a list of sites that are blocked from pipelining, i.e sites that are known to not support HTTP pipelining. The array is copied by libcurl.

Pass a NULL pointer to clear the block list.

DEFAULT

NULL, which means that there is no block list.

PROTOCOLS

This functionality affects http only

EXAMPLE

```
static char *site_block_list[] =
{
    "www.haxx.se",
    "www.example.com:1234",
    NULL
};

int main(void)
{
    CURLM *m = curl_multi_init();
    curl_multi_setopt(m, CURLMOPT_PIPELINING_SITE_BL, site_block_list);
}
```

AVAILABILITY

Added in curl 7.30.0

RETURN VALUE

curl_multi_setopt(3) returns a CURLMcode indicating success or error.

CURLM_OK (0) means everything was OK, non-zero means an error occurred, see *libcurl-errors(3)*.

SEE ALSO

CURLMOPT_PIPELINING(3), CURLMOPT_PIPELINING_SERVER_BL(3)