

NAME

CURLLOPT_HTTP_TRANSFER_DECODING – HTTP transfer decoding control

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLLOPT_HTTP_TRANSFER_DECODING,  
                           long enabled);
```

DESCRIPTION

Pass a long to tell libcurl how to act on transfer decoding. If set to zero, transfer decoding is disabled, if set to 1 it is enabled (default). libcurl does chunked transfer decoding by default unless this option is set to zero.

DEFAULT

1

PROTOCOLS

This functionality affects http only

EXAMPLE

```
int main(void)
{
    CURL *curl = curl_easy_init();
    if(curl) {
        CURLcode result;
        curl_easy_setopt(curl, CURLOPT_URL, "https://example.com/");
        curl_easy_setopt(curl, CURLOPT_HTTP_TRANSFER_DECODING, 0L);
        result = curl_easy_perform(curl);
    }
}
```

AVAILABILITY

Added in curl 7.16.2

RETURN VALUE

curl_easy_setopt(3) returns a CURLcode indicating success or error.

CURLE_OK (0) means everything was OK, non-zero means an error occurred, see *libcurl-errors(3)*.

SEE ALSO

CURLLOPT_ACCEPT_ENCODING(3), CURLLOPT_HTTP_CONTENT_DECODING(3)