

NAME

CURLOPT_NOPROGRESS – switch off the progress meter

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_NOPROGRESS, long onoff);
```

DESCRIPTION

If *onoff* is to 1, it tells the library to shut off the progress meter completely for requests done with this *handle*. It also prevents the *CURLOPT_XFERINFOFUNCTION(3)* or *CURLOPT_PROGRESSFUNCTION(3)* from getting called.

DEFAULT

1, meaning it normally runs without a progress meter.

PROTOCOLS

This functionality affects all supported protocols

EXAMPLE

```
int main(void)
{
    CURL *curl = curl_easy_init();
    if(curl) {
        CURLcode result;
        curl_easy_setopt(curl, CURLOPT_URL, "https://example.com");

        /* enable progress meter */
        curl_easy_setopt(curl, CURLOPT_NOPROGRESS, 0L);

        /* Perform the request */
        result = curl_easy_perform(curl);
        curl_easy_cleanup(curl);
    }
}
```

AVAILABILITY

Added in curl 7.1

RETURN VALUE

curl_easy_setopt(3) returns a CURLcode indicating success or error.

CURLE_OK (0) means everything was OK, non-zero means an error occurred, see *libcurl-errors(3)*.

SEE ALSO

CURLOPT_DEBUGFUNCTION(3), CURLOPT_PROGRESSFUNCTION(3), CURLOPT_VERBOSE(3), CURLOPT_XFERINFOFUNCTION(3)