

NAME

CURLOPT_RTSP_CLIENT_CSEQ – RTSP client CSEQ number

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_RTSP_CLIENT_CSEQ, long cseq);
```

DESCRIPTION

Pass a long to set the CSEQ number to issue for the next RTSP request. Useful if the application is resuming a previously broken connection. The CSEQ increments from this new number henceforth.

DEFAULT

0

PROTOCOLS

This functionality affects rtsp only

EXAMPLE

```
int main(void)
{
    CURL *curl = curl_easy_init();
    if(curl) {
        CURLcode result;
        curl_easy_setopt(curl, CURLOPT_URL, "rtsp://example.com/");
        curl_easy_setopt(curl, CURLOPT_RTSP_CLIENT_CSEQ, 1234L);
        result = curl_easy_perform(curl);
        curl_easy_cleanup(curl);
    }
}
```

AVAILABILITY

Added in curl 7.20.0

RETURN VALUE

curl_easy_setopt(3) returns a CURLcode indicating success or error.

CURLE_OK (0) means everything was OK, non-zero means an error occurred, see *libcurl-errors(3)*.

SEE ALSO

CURLINFO_RTSP_CLIENT_CSEQ(3), **CURLINFO_RTSP_SERVER_CSEQ(3),** **CURLINFO_RTSP_REQUEST(3),** **CURLOPT_RTSP_SERVER_CSEQ(3)**