

NAME

atexit – register a function to be called at normal process termination

LIBRARY

Standard C library (*libc*, *-lc*)

SYNOPSIS

```
#include <stdlib.h>
```

```
int atexit(typeof(void (void)) *function);
```

DESCRIPTION

The **atexit()** function registers the given *function* to be called at normal process termination, either via **exit(3)** or via return from the program's *main()*. Functions so registered are called in the reverse order of their registration; no arguments are passed.

The same function may be registered multiple times: it is called once for each registration.

POSIX.1 requires that an implementation allow at least **ATEXIT_MAX** (32) such functions to be registered. The actual limit supported by an implementation can be obtained using **sysconf(3)**.

When a child process is created via **fork(2)**, it inherits copies of its parent's registrations. Upon a successful call to one of the **exec(3)** functions, all registrations are removed.

RETURN VALUE

The **atexit()** function returns the value 0 if successful; otherwise, it returns a nonzero value.

ATTRIBUTES

For an explanation of the terms used in this section, see **attributes(7)**.

Interface	Attribute	Value
atexit()	Thread safety	MT-Safe

VERSIONS

POSIX.1 says that the result of calling **exit(3)** more than once (i.e., calling **exit(3)** within a function registered using **atexit()**) is undefined. On some systems (but not Linux), this can result in an infinite recursion; portable programs should not invoke **exit(3)** inside a function registered using **atexit()**.

STANDARDS

C11, POSIX.1-2008.

HISTORY

POSIX.1-2001, C89, C99, SVr4, 4.3BSD.

NOTES

Functions registered using **atexit()** (and **on_exit(3)**) are not called if a process terminates abnormally because of the delivery of a signal.

If one of the registered functions calls **_exit(2)**, then any remaining functions are not invoked, and the other process termination steps performed by **exit(3)** are not performed.

The **atexit()** and **on_exit(3)** functions register functions on the same list: at normal process termination, the registered functions are invoked in reverse order of their registration by these two functions.

According to POSIX.1, the result is undefined if **longjmp(3)** is used to terminate execution of one of the functions registered using **atexit()**.

Linux notes

Since glibc 2.2.3, **atexit()** (and **on_exit(3)**) can be used within a shared library to establish functions that are called when the shared library is unloaded.

EXAMPLES

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
```

```
static void
bye(void)
{
    printf("That was all, folks\n");
}

int
main(void)
{
    long a;
    int i;

    a = sysconf(_SC_ATEXIT_MAX);
    printf("ATEXIT_MAX = %ld\n", a);

    i = atexit(bye);
    if (i != 0) {
        fprintf(stderr, "cannot set exit function\n");
        exit(EXIT_FAILURE);
    }

    exit(EXIT_SUCCESS);
}
```

SEE ALSO

[_exit\(2\)](#), [dlopen\(3\)](#), [exit\(3\)](#), [on_exit\(3\)](#)