

NAME

autoupdate – Update a configure.ac to a newer Autoconf

SYNOPSIS

autoupdate [*OPTION*]... [*TEMPLATE-FILE*]...

DESCRIPTION

Update each *TEMPLATE-FILE* if given, or 'configure.ac' if present, or else 'configure.in', to the syntax of the current version of Autoconf. The original files are backed up.

Operation modes:

- h, --help**
print this help, then exit
- V, --version**
print version number, then exit
- v, --verbose**
verbosely report processing
- d, --debug**
don't remove temporary files
- f, --force**
consider all files obsolete

Library directories:

- B, --prepend-include=DIR**
prepend directory DIR to search path
- I, --include=DIR**
append directory DIR to search path

AUTHOR

Written by David J. MacKenzie and Akim Demaille.

REPORTING BUGS

Report bugs to bug-autoconf@gnu.org, or via Savannah: <https://savannah.gnu.org/support/?group=autoconf>.

COPYRIGHT

Copyright © 2023 Free Software Foundation, Inc. License GPLv3+/Autoconf: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>, <<https://gnu.org/licenses/exceptions.html>>

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

autoconf(1), **automake(1)**, **autoreconf(1)**, **autoupdate(1)**, **autoheader(1)**, **autoscan(1)**, **config.guess(1)**, **config.sub(1)**, **ifnames(1)**, **libtool(1)**.

The full documentation for Autoconf is maintained as a Texinfo manual. To read the manual locally, use the command

info autoconf

You can also consult the Web version of the manual at <https://gnu.org/software/autoconf/manual/>.