

NAME

avahi-dnsconfd.action – avahi-dnsconfd action script

SYNOPSIS

/etc/avahi/avahi-dnsconfd.action

DESCRIPTION

avahi-dnsconfd.action is the action script that is called whenever a new unicast DNS server is found or removed by avahi-dnsconfd. The default script as shipped with avahi patches */etc/resolv.conf* to reflect the changed unicast DNS server configuration.

PARAMETERS

argv[1] Contains the character "+" if the DNS server is new, "-" when it shall be removed from the DNS server list.

argv[2] The IP address of the DNS server.

argv[3] Numerical network interface number this DNS server was found on.

argv[4] Numerical protocol number this DNS server was found on. (usually 2 for IPv4 and 10 for IPv6)

ENVIRONMENT

AVAHI_INTERFACE Contains the textual interface name the corresponds with argv[3]. (e.g. "eth0")

AVAHI_INTERFACE_DNS_SERVERS Contains a list of all DNS servers that avahi-dnsconfd found on the interface **\$AVAHI_INTERFACE**, separated by spaces.

AVAHI_DNS_SERVERS Contains a list of all DNS server that avahi-dnsconfd found on all interfaces, separated by spaces.

AUTHORS

The Avahi Developers <avahi (at) lists (dot) freedesktop (dot) org>; Avahi is available from <http://avahi.org/>

SEE ALSO

avahi-dnsconfd(8), avahi-daemon(8)

COMMENTS

This man page was written using **xml2man(1)** by Oliver Kurth.