

NAME

blkzone – run zone command on a device

SYNOPSIS

blkzone *command* [*options*] *device*

DESCRIPTION

blkzone is used to run zone command on device that support the Zoned Block Commands (ZBC) or Zoned-device ATA Commands (ZAC). The zones to operate on can be specified using the offset, count and length options.

The *device* argument is the pathname of the block device.

COMMANDS**report**

The command **blkzone report** is used to report device zone information.

By default, the command will report all zones from the start of the block device. Options may be used to modify this behavior, changing the starting zone or the size of the report, as explained below.

Report output:

start	Zone start sector
len	Zone length in number of sectors
cap	Zone capacity in number of sectors
wptr	Zone write pointer position
reset	Reset write pointer recommended
non-seq	Non-sequential write resources active
cond	Zone condition
type	Zone type

Zone conditions:

cl	Closed
nw	Not write pointer
em	Empty
fu	Full
oe	Explicitly opened
oi	Implicitly opened
ol	Offline
ro	Read only
x?	Reserved conditions (should not be reported)

capacity

The command **blkzone capacity** is used to report device capacity information.

By default, the command will report the sum, in number of sectors, of all zone capacities on the device. Options may be used to modify this behavior, changing the starting zone or the size of the report, as explained below.

reset

The command **blkzone reset** is used to reset one or more zones. Unlike **sg_reset_wp(8)**, this command operates from the block layer and can reset a range of zones.

open

The command **blkzone open** is used to explicitly open one or more zones. Unlike **sg_zone(8)**, open action, this command operates from the block layer and can open a range of zones.

close

The command **blkzone close** is used to close one or more zones. Unlike **sg_zone(8)**, close action, this command operates from the block layer and can close a range of zones.

finish

The command **blkzone finish** is used to finish (transition to full condition) one or more zones. Unlike **sg_zone(8)**, finish action, this command operates from the block layer and can finish a range of zones.

By default, the **reset**, **open**, **close** and **finish** commands will operate from the zone at device sector 0 and operate on all zones. Options may be used to modify this behavior as explained below.

OPTIONS

The *offset* and *length* option arguments may be followed by the multiplicative suffixes KiB (=1024), MiB (=1024*1024), and so on for GiB, TiB, PiB, EiB, ZiB and YiB (the "iB" is optional, e.g., "K" has the same meaning as "KiB") or the suffixes KB (=1000), MB (=1000*1000), and so on for GB, TB, PB, EB, ZB and YB. Additionally, the 0x prefix can be used to specify *offset* and *length* in hex.

-o, --offset *sector*

The starting zone specified as a sector offset. The provided offset in sector units (512 bytes) should match the start of a zone. The default value is zero.

-l, --length *sectors*

The maximum number of sectors the command should operate on. The default value is the number of sectors remaining after *offset*. This option cannot be used together with the option **--count**.

-c, --count *count*

The maximum number of zones the command should operate on. The default value is the number of zones starting from *offset*. This option cannot be used together with the option **--length**.

-f, --force

Enforce commands to change zone status on block devices used by the system.

-v, --verbose

Display the number of zones returned in the report or the range of sectors reset.

-h, --help

Display help text and exit.

-V, --version

Display version and exit.

AUTHORS

Shaun Tancheff <shaun@tancheff.com>, Karel Zak <kzak@redhat.com>

SEE ALSO

sg_rep_zones(8)

REPORTING BUGS

For bug reports, use the issue tracker <<https://github.com/util-linux/util-linux/issues>>.

AVAILABILITY

The **blkzone** command is part of the **util-linux** package which can be downloaded from Linux Kernel Archive <<https://www.kernel.org/pub/linux/utils/util-linux/>>.