

NAME

chroot – run command or interactive shell with special root directory

SYNOPSIS

chroot [*OPTION*]... *NEWROOT* [*COMMAND* [*ARG*]...]

DESCRIPTION

Run *COMMAND* with root directory set to *NEWROOT*.

--groups=G_LIST

specify supplementary groups as g1,g2,...,gN

--userspec=USER:GROUP

specify user and group (ID or name) to use

--skip-chdir

do not change working directory to '/'

--help display this help and exit

--version

output version information and exit

If no command is given, run `""$SHELL" -i` (default: `/bin/sh -i`).

Exit status:

- 125 if the chroot command itself fails
- 126 if *COMMAND* is found but cannot be invoked
- 127 if *COMMAND* cannot be found
- the exit status of *COMMAND* otherwise

AUTHOR

Written by Roland McGrath.

REPORTING BUGS

Report bugs to: bug-coreutils@gnu.org

Report Gentoo bugs to: <https://bugs.gentoo.org/>

GNU coreutils home page: <https://www.gnu.org/software/coreutils/>

General help using GNU software: <https://www.gnu.org/gethelp/>

Report any translation bugs to <https://translationproject.org/team/>

SEE ALSO

chroot(2)

Full documentation <https://www.gnu.org/software/coreutils/chroot>
or available locally via: `info '(coreutils) chroot invocation'`

Packaged by Gentoo (9.11–r1 (p0))

Copyright © 2026 Free Software Foundation, Inc.

License GPLv3+: GNU GPL version 3 or later <https://gnu.org/licenses/gpl.html>.

This is free software: you are free to change and redistribute it.

There is NO WARRANTY, to the extent permitted by law.