

NAME

ctrlaltdel – set the function of the Ctrl–Alt–Del combination

SYNOPSIS

ctrlaltdel **hard|soft**

DESCRIPTION

Based on examination of the *linux/kernel/reboot.c* code, it is clear that there are two supported functions that the <Ctrl–Alt–Del> sequence can perform.

hard

Immediately reboot the computer without calling **sync**(2) and without any other preparation. This is the default.

soft

Make the kernel send the **SIGINT** (interrupt) signal to the **init** process (this is always the process with PID 1). If this option is used, the **init**(8) program must support this feature. Since there are now several **init**(8) programs in the Linux community, please consult the documentation for the version that you are currently using.

When the command is run without any argument, it will display the current setting.

The function of **ctrlaltdel** is usually set in the */etc/rc.local* file.

OPTIONS

-h, --help

Display help text and exit.

-V, --version

Display version and exit.

FILES

/etc/rc.local

AUTHORS

Peter Orbaek <poe@daimi.aau.dk>

SEE ALSO

init(8), **systemd**(1)

REPORTING BUGS

For bug reports, use the issue tracker <<https://github.com/util-linux/util-linux/issues>>.

AVAILABILITY

The **ctrlaltdel** command is part of the util–linux package which can be downloaded from Linux Kernel Archive <<https://www.kernel.org/pub/linux/utils/util-linux/>>.