

NAME

cupsaccept/cupsreject – accept/reject jobs sent to a destination

SYNOPSIS

cupsaccept [**-E**] [**-U** *username*] [**-h** *hostname[:port]*] *destination(s)*

cupsreject [**-E**] [**-U** *username*] [**-h** *hostname[:port]*] [**-r** *reason*] *destination(s)*

DESCRIPTION

The **cupsaccept** command instructs the printing system to accept print jobs to the specified destinations.

The **cupsreject** command instructs the printing system to reject print jobs to the specified destinations. The **-r** option sets the reason for rejecting print jobs. If not specified, the reason defaults to "Reason Unknown".

OPTIONS

The following options are supported by both **cupsaccept** and **cupsreject**:

-E Forces encryption when connecting to the server.

-U *username*

Sets the username that is sent when connecting to the server.

-h *hostname[:port]*

Chooses an alternate server.

-r "*reason*"

Sets the reason string that is shown for a printer that is rejecting jobs.

CONFORMING TO

The **cupsaccept** and **cupsreject** commands correspond to the System V printing system commands "accept" and "reject", respectively. Unlike the System V printing system, CUPS allows printer names to contain any printable character except SPACE, TAB, "/", or "#". Also, printer and class names are *not* case-sensitive.

Finally, the CUPS versions may ask the user for an access password depending on the printing system configuration.

SEE ALSO

cancel(1), **cupsenable**(8), **lp**(1), **lpadmin**(8), **lpstat**(1),
CUPS Online Help (<http://localhost:631/help>)

COPYRIGHT

Copyright © 2020-2024 by OpenPrinting.