

NAME

`dbus-update-activation-environment` – update environment used for D-Bus session services

SYNOPSIS

dbus-update-activation-environment [`--systemd`] [`--verbose`] `--all` | `VAR...` | `VAR=VAL...`

DESCRIPTION

dbus-update-activation-environment updates the list of environment variables used by **dbus-daemon** `--session` when it activates session services without using **systemd**.

With the `--systemd` option, if an instance of **systemd** `--user` is available on D-Bus, it also updates the list of environment variables used by **systemd** `--user` when it activates user services, including D-Bus session services for which **dbus-daemon** has been configured to delegate activation to **systemd**. This is very similar to the **import-environment** command provided by **systemctl**(1).

Variables that are special to **dbus-daemon** or **systemd** may be set, but their values will be overridden when a service is started. For instance, it is not useful to add `DBUS_SESSION_BUS_ADDRESS` to **dbus-daemon**'s activation environment, although it might still be useful to add it to **systemd**'s activation environment.

OPTIONS**--all**

Set all environment variables present in the environment used by **dbus-update-activation-environment**.

--systemd

Set environment variables for **systemd** user services as well as for traditional D-Bus session services.

--verbose

Output messages to standard error explaining what **dbus-update-activation-environment** is doing.

VAR

If `VAR` is present in the environment of **dbus-update-activation-environment**, set it to the same value for D-Bus services. Its value must be UTF-8 (if not, it is skipped with a warning). If `VAR` is not present in the environment, this argument is silently ignored.

VAR=VAL

Set `VAR` to `VAL`, which must be UTF-8.

EXAMPLES

dbus-update-activation-environment is primarily designed to be used in Linux distributions' X11 session startup scripts, in conjunction with the "user bus" design.

To propagate **DISPLAY** and **XAUTHORITY** to **dbus-daemon** and, if present, **systemd**, and propagate **DBUS_SESSION_BUS_ADDRESS** to **systemd**:

```
dbus-update-activation-environment --systemd \
    DBUS_SESSION_BUS_ADDRESS DISPLAY XAUTHORITY
```

To propagate all environment variables except **XDG_SEAT**, **XDG_SESSION_ID** and **XDG_VTNR** to **dbus-daemon** (and, if present, **systemd**) for compatibility with legacy X11 session startup scripts:

```
# in a subshell so the variables remain set in the
# parent script
(
    unset XDG_SEAT
    unset XDG_SESSION_ID
    unset XDG_VTNR
```

```
dbus-update-activation-environment --systemd --all  
)
```

EXIT STATUS

dbus-update-activation-environment exits with status 0 on success, EX_USAGE (64) on invalid command-line options, EX_OSERR (71) if unable to connect to the session bus, or EX_UNAVAILABLE (69) if unable to set the environment variables. Other nonzero exit codes might be added in future versions.

ENVIRONMENT

DBUS_SESSION_BUS_ADDRESS, **XDGRUNTIME_DIR** and/or **DISPLAY** are used to find the address of the session bus.

LIMITATIONS

dbus-daemon does not provide a way to unset environment variables after they have been set (although **systemd** does), so **dbus-update-activation-environment** does not offer this functionality either.

POSIX does not specify the encoding of non-ASCII environment variable names or values and allows them to contain any non-zero byte, but neither **dbus-daemon** nor **systemd** supports environment variables with non-UTF-8 names or values. Accordingly, **dbus-update-activation-environment** assumes that any name or value that appears to be valid UTF-8 is intended to be UTF-8, and ignores other names or values with a warning.

BUGS

Please send bug reports to the D-Bus bug tracker or mailing list. See <https://www.freedesktop.org/wiki/Software/dbus/>.

AUTHOR

See <https://dbus.freedesktop.org/doc/AUTHORS>

SEE ALSO

dbus-daemon(1), **systemd**(1), the **import-environment** command of **systemctl**(1)

COPYRIGHT

Copyright © 2015 Collabora Ltd.

This man page is distributed under the same terms as **dbus-update-activation-environment** (MIT/X11). There is NO WARRANTY, to the extent permitted by law.