

NAME

docker-image-load - Load an image from a tar archive or STDIN

SYNOPSIS

docker image load [OPTIONS]

DESCRIPTION

Loads a tarred repository from a file or the standard input stream. Restores both images and tags. Write image names or IDs imported it standard output stream.

EXAMPLES

```
$ docker images
REPOSITORY          TAG                IMAGE ID           CREATED           SIZE
busybox              latest             769b9341d937      7 weeks ago      2.48
$ docker load --input fedora.tar
# [...]
Loaded image: fedora:rawhide
# [...]
Loaded image: fedora:20
# [...]
$ docker images
REPOSITORY          TAG                IMAGE ID           CREATED           SIZE
busybox              latest             769b9341d937      7 weeks ago      2.48
fedora               rawhide            0d20aec6529d      7 weeks ago      387
fedora               20                 58394af37342      7 weeks ago      385.
fedora               heisenbug          58394af37342      7 weeks ago      385.
fedora               latest             58394af37342      7 weeks ago      385.
```

See also

docker-image-save(1) to save one or more images to a tar archive (streamed to STDOUT by default).

OPTIONS

-i, --input="" Read from tar archive file, instead of STDIN

--platform=[] Load only the given platform(s). Formatted as a comma-separated list of "os[/arch[/variant]]" (e.g., "linux/amd64,linux/arm64/v8").

-q, --quiet[=false] Suppress the load output

SEE ALSO

docker-image(1)