

NAME

ebump – Gentoo: Ebuild revision bumper

SYNTAX

ebump [*option*] <*package-name*[-*version*]>

DESCRIPTION

ebump bumps the revision of a particular ebuild, and all auxiliary files in the files/ directory that have a matching version suffix.

By default, the all new revision files will be added to the VCS.

You must stand in the directory of the ebuild to be bumped.

OPTIONS

-C

--no-vcs

Do not add new files to VCS.

-V

--version

Display version information and exit.

-v

--verbose

Increase verbosity level. May be used more than once.

-q

--quiet

Do not output any non-essential information.

-a

--no-auxfiles

don't bump auxfiles (files/*)

-d

--delete-old

Delete old revision and old auxiliary files from VCS. This is *dangerous* and should only be used if you know exactly what you are doing, because

- 1) the old revision may be stable on a different architecture than the one you are working on.
- 2) the auxiliary files may be required by other versions of the ebuild.
- 3) the new revision should usually undergo a period of testing before being marked stable.

CONFIGURATION

/etc/gentoolkit/ebump.conf

~/.gentoo/ebump.conf

From these files, *ebump* will load the settings

opt_verbosity (default 1) - verbosity level 0-10

opt_add_vcs (default *y*) - add new files to VCS
opt_bump_auxfiles (default *y*) - bump auxiliary files in files/
opt_delete_old (default *n*) - delete old revision (DANGEROUS!)

SEE ALSO

The rest of the utilities in *app-portage/gentoolkit-dev*, such as *ekeyword(1)*.

AUTHORS

Karl Trygve Kalleberg <karltk@gentoo.org>

Christian Ruppert <idl0r@gentoo.org>