

NAME

CURLOPT_CRLF – CRLF conversion

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_CRLF, long conv);
```

DESCRIPTION

Pass a long. If the value is set to 1 (one), libcurl converts Unix newlines to CRLF newlines on transfers. Disable this option again by setting the value to 0 (zero).

This is a legacy option of questionable use.

DEFAULT

0

PROTOCOLS

This functionality affects all supported protocols

EXAMPLE

```
int main(void)
{
    CURL *curl = curl_easy_init();
    if(curl) {
        CURLcode result;
        curl_easy_setopt(curl, CURLOPT_URL, "ftp://example.com/");
        curl_easy_setopt(curl, CURLOPT_CRLF, 1L);
        result = curl_easy_perform(curl);
        curl_easy_cleanup(curl);
    }
}
```

AVAILABILITY

Added in curl 7.1

RETURN VALUE

curl_easy_setopt(3) returns a CURLcode indicating success or error.

CURLE_OK (0) means everything was OK, non-zero means an error occurred, see *libcurl-errors(3)*.

SEE ALSO

CURLOPT_CONV_FROM_NETWORK_FUNCTION(3),
WORK_FUNCTION(3)

CURLOPT_CONV_TO_NETWORK_FUNCTION(3)