

NAME

CURLLOPT_EXPECT_100_TIMEOUT_MS – timeout for Expect: 100–continue response

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLLOPT_EXPECT_100_TIMEOUT_MS,  
                           long milliseconds);
```

DESCRIPTION

Pass a long to tell libcurl the number of *milliseconds* to wait for a server response with the HTTP status 100 (Continue), 417 (Expectation Failed) or similar after sending an HTTP request containing an Expect: 100–continue header. If this times out before a response is received, the request body is sent anyway.

DEFAULT

1000 milliseconds

PROTOCOLS

This functionality affects http only

EXAMPLE

```
int main(void)
{
    CURL *curl = curl_easy_init();
    if(curl) {
        CURLcode result;
        curl_easy_setopt(curl, CURLLOPT_URL, "https://example.com");

        /* wait 3 seconds for 100-continue */
        curl_easy_setopt(curl, CURLLOPT_EXPECT_100_TIMEOUT_MS, 3000L);

        result = curl_easy_perform(curl);
        curl_easy_cleanup(curl);
    }
}
```

AVAILABILITY

Added in curl 7.36.0

RETURN VALUE

curl_easy_setopt(3) returns a CURLcode indicating success or error.

CURLE_OK (0) means everything was OK, non-zero means an error occurred, see *libcurl-errors(3)*.

SEE ALSO

CURLLOPT_HTTPPOST(3), CURLLOPT_POST(3)