

NAME

asn1_der_decoding_element – API function

SYNOPSIS

```
#include <libtasn1.h>
```

```
int asn1_der_decoding_element(asn1_node * structure, const char * elementName, const void * ider,
int len, char * errorDescription);
```

ARGUMENTS

asn1_node * structure
 pointer to an ASN1 structure

const char * elementName
 name of the element to fill

const void * ider
 vector that contains the DER encoding of the whole structure.

int len
 number of bytes of *der: der[0]..der[len-1]

char * errorDescription
 null-terminated string contains details when an error occurred.

DESCRIPTION

Fill the element named *ELEMENTNAME* with values of a DER encoding string. The structure must just be created with function **asn1_create_element()**. The DER vector must contain the encoding string of the whole *STRUCTURE*. If an error occurs during the decoding procedure, the * *STRUCTURE* is deleted and set equal to **NULL**.

This function is deprecated and may just be an alias to `asn1_der_decoding` in future versions. Use **asn1_der_decoding()** instead.

RETURNS

ASN1_SUCCESS if DER encoding OK, **ASN1_ELEMENT_NOT_FOUND** if *ELEMENT* is **NULL** or *elementName* == **NULL**, and **ASN1_TAG_ERROR** or **ASN1_DER_ERROR** if the der encoding doesn't match the structure *structure* (**ELEMENT* deleted).

COPYRIGHT

Copyright © 2006-2025 Free Software Foundation, Inc..

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **libtasn1** is maintained as a Texinfo manual. If the **info** and **libtasn1** programs are properly installed at your site, the command

```
info libtasn1
```

should give you access to the complete manual. As an alternative you may obtain the manual from:

```
https://www.gnu.org/software/libtasn1/manual/
```