

NAME

bashcomp.eselect – Manage contributed bash-completion scripts

SYNOPSIS

```
eselect bashcomp [help|usage|version]
eselect bashcomp list [--global|--user]
eselect bashcomp enable [--global|--user] bashcomp...
eselect bashcomp disable [--global|--user] bashcomp...
```

DESCRIPTION

eselect bashcomp is Gentoo's tool for managing enabled completions for bash.

ACTION: LIST

```
eselect bashcomp list [--global|--user]
```

Display a list of available contributed bash-completion scripts. Enabled bash-completions are marked with a '*'.

If the **--global** option is specified, only global configuration is used to determine whether completions are enabled. If the **--user** option is specified, only user-specific configuration is used. If neither of the two options is specified, both global and user-specific configurations are used and the effective state for the current user is displayed.

```
$ eselect bashcomp list
```

Available completions:

```
[1] bitkeeper
```

```
[2] cowsay *
```

ACTION: ENABLE

```
eselect bashcomp enable [--global|--user] bashcomp...
```

Enable the specified completion(s). Parameters may include completion names or numbers corresponding to the list output by **eselect bashcomp list**.

If the **--global** option is specified, the global configuration is modified. If the **--user** option is specified, the user-specific configuration is modified. This includes whitelisting the module if necessary. If neither of the two options is specified, the default is to alter the global configuration when run by superuser or the user configuration otherwise.

ACTION: DISABLE

```
eselect bashcomp disable [--global|--user] bashcomp...
```

Disable the specified completion(s). Parameters may include completion names or numbers corresponding to the list output by **eselect bashcomp list**.

If the **--global** option is specified, the global configuration is modified. If the **--user** option is specified, the user-specific configuration is modified. This includes whitelisting the module if necessary. If neither of the two options is specified, the default is to alter the global configuration when run by superuser or the user configuration otherwise.

ACTION: PRUNE

```
eselect bashcomp prune [--global|--user]
```

Prune the configuration, removing outdated and redundant entries.

If the **--global** option is specified, the global configuration is pruned. If the **--user** option is specified, the user-specific configuration is pruned. If neither of the two options is specified, both configurations are cleaned.

AUTHOR

Michał Górny <mgorny@gentoo.org>

bashcomp.eselect(5)

`eselect`

bashcomp.eselect(5)

SEE ALSO

`eselect(1)`