

NAME

CURLINFO_SIZE_UPLOAD – number of uploaded bytes

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_getinfo(CURL *handle, CURLINFO_SIZE_UPLOAD,  
                           double *uploadp);
```

DESCRIPTION

Pass a pointer to a double to receive the total amount of bytes that were uploaded.

CURLINFO_SIZE_UPLOAD_T(3) is a newer replacement that returns a more sensible variable type.

PROTOCOLS

This functionality affects all supported protocols

EXAMPLE

```
int main(void)  
{  
    CURL *curl = curl_easy_init();  
    if(curl) {  
        CURLcode result;  
        curl_easy_setopt(curl, CURLOPT_URL, "https://example.com");  
  
        /* Perform the request */  
        result = curl_easy_perform(curl);  
  
        if(result == CURLE_OK) {  
            double ul;  
            result = curl_easy_getinfo(curl, CURLINFO_SIZE_UPLOAD, &ul);  
            if(result == CURLE_OK) {  
                printf("Uploaded %.0f bytes\n", ul);  
            }  
        }  
    }  
}
```

DEPRECATED

Deprecated since 7.55.0.

AVAILABILITY

Added in curl 7.4.1

RETURN VALUE

curl_easy_getinfo(3) returns a CURLcode indicating success or error.

CURLE_OK (0) means everything was OK, non-zero means an error occurred, see *libcurl-errors(3)*.

SEE ALSO

CURLINFO_SIZE_DOWNLOAD_T(3), *CURLINFO_SIZE_UPLOAD_T(3)*, *curl_easy_getinfo(3)*,
curl_easy_setopt(3)